Airline Hydraulic's Main Page **Basic Symbols** Lines -continuous line - flow line -dashed line - pilot, drain -envelope - long and short dashes around two or more component symbols. Circular -large circle pump, motor -small circle -Measuring devices -semi-circle rotary actuator **Square** -one square - pressure control function -two or three adjacent squares directional control **Diamond** -diamond -Fluid conditioner (filter, separator, lubricator, heat exchanger) **Miscellaneous Symbols** -Spring -Flow Restriction

Triangle

•

-solid -

Direction of Hydraulic Fluid Flow

-open -

 ∇

Direction of Pnematic flow

Pumps and Compressors

Fixed Displacement hydraulic pump

Φ

. . . .

unidirectional

③

bidirectional

Variable displacement hydraulic pump



-

unidirectional



_

bidirectional

Compressor



Motors

Fixed displacement hydraulic motor



-

unidirectional



bidirectional

Variable displacement hydraulic motor



unidirectional



-bidirectional

Pneumatic motor



unidirectional



-bidirectional

Rotary Actuator



- hydraulic




- pneumatic

Cylinders

Single acting cylinder



-returned by external force




-returned by spring or extended by spring force

Double acting cylinders



-single piston rod (fluid required to extend and retract)




-double ended piston rod

Cylinders with cushions




- single fixed cushon




Directional Control Valves

Directional control valve (2 ports / 2 positions)



Directional control valve (3 ports / 2 positions)



Directional control valve (4 ports / 2 positions)



-directional control valve with 4 ports and 2 finite postions

Directional control valve (4 ports / 3 positions)



-directional control valve with 4 ports and 3 finite postions *-(center position can have various flow paths)

Directional control valve (5 ports / 2 positions) Normally a pneumatic valve



-directional control valve with 5 ports and 2 finite postions

Directional control valve (5 ports / 3 positions) Normally a pneumatic valve




-directional control valve with 5 ports and 3 finite postions

Proportional directional control valve

Electro-hydraulic servo valve

-The spool positions on these valves is variable allowing for variable flow conditions.




-single-stage

direct
operation
unit which
accepts an
analog
signal and
provides a
similar
analog fluid
power
output

-two-stage with mechnical feedback

feedback indirect pilot operation unit which accepts an

accepts an analog signal and provides a similar analog fluid power output



Control Methods

Manual Control



-general symbol

(without showing the control type)



-pushbutton



-lever




-foot pedal

Mechanical Control



-plunger or tracer



blocked flow in other direction






-pilot operated check valve, pilot to close -pilot operated check valve, pilot to open

Shuttle valve



-to isolate one part of a system from an alternate part of circuit.

Rapid exhaust valve/Pneumatic



-installed close to an actuator for rapid movement of the actuator.

Pressure Control Valves

Pressure Relief Valve(safety valve) normally closed



- line
pressure is
limited to
the setting
of the
valve,
secondary
part is
directed to
tank.

Proportional Pressure Relief



- line pressure is limited to and proportional to an electronic signal

Sequence Valve



- when the line pressure reaches the setting of the valve, valve opens permitting flow to the secondary port. The pilot must be externally drained to tank.

pressure downstream

Pressure Reducing valve of valve is

of valve is limited to the setting of the valve



Flow Control Valves

Throttle valve



-adjustable output flow

Flow Control valve

-with fixed (variations in


output and relief port to reservoir with relief for excess flow (variations in inlet

- compensated flow control fixed output regardless
- temperature compensated
- -with variable output and relief port to reservoir

Flow dividing valve



-flow is divided equally to two outputs.



Shut-Off Valve



-Simplified symbol

Accumulators



Filters, Water Traps, Lubricators and Miscellaneous Apparatus

Filter or Strainer



Water Trap



-with manual drain



-with automatic drained

Filter with water trap



-with manual drain



-automatic drain

Air Dryer




refrigerant, or chemical removal of water from compressed air line

Lubricator



Conditioning unit

-oil vapor is indected into air line





-compound symbol of filter, regulator, lubricator unit

-Simplified Symbol

Heat Exchangers



-air or water cooled unit designed to remove heat from oil returning to reservoir

Hydraulics | Pneumatics | Electro Controls | Marine
& Mobile | Fluid Connectors | Safety Systems |
Training | Repair & Field Service



If you would like a Sales Quote, please email

Request Sales Quote

If you have any questions, comments, or suggestions about this page please

Send E-mail to the Webmaster

Copyright © 1997 Airline Hydraulics Corporation

<u>Legal</u> <u>Disclaimer</u>